DesignLights Consortium





Classification	Standard
Primary Use	Retrofit Kits for Fuel Pump Canopy Luminaires
Reported Input Wattage	120.2 W
Reported Light Output	15250 lm
Reported CCT	5000 K
Reported CRI (Ra)	83
Product ID	PFV8LGV1
DLC Family Code	HHHCWC
Listing Status	Listed
Date Qualified	2020-03-30

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PFV8LGV1
Manufacturer	ESL Vision
Brand	ESL Vision
Model Number	ESL-MUR-120W-350
Parent	No
Classification	Standard
DLC Family Code	нннсмс
Input Power Type	AC
Notes	Product Updated 7/27/2022

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Retrofit Kit
General Application	High Output
Primary Use Designation	Retrofit Kits for Fuel Pump Canopy Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Exterior Photocell,Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	15250 lm
Reported Efficacy (AC)	126.87 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	83
Reported R9	8
Reported IES Rf	84
Reported IES Rg	96
Reported IES Rcs,h1	-12
Reported Default Light Output	15250 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	120.2 W
Reported Total Harmonic Distortion	14.5 %
Reported Power Factor	0.927
Reported Default Input Wattage	120.2 W
Voltage Range	120-277 V

LISTING INFORMATION VIEW DETAILS

Testing in a Manufacturer-Selected Housing (Luminaire Specific)	General Purpose
---	-----------------

VERSION HISTORY VIEW DETAILS

2022-07-27	Listed	5.1	Standard
2022-06-30	Delisted	5	Standard
2020-03-30	Listed	5	Standard
2018-11-02	Listed	4.4	Standard

2018-06-15 Listed 4.3 Standard	2010-00-13			
--------------------------------	------------	--	--	--