DesignLights Consortium





Classification	Standard
Primary Use	Retrofit Kits for High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	281.8 W
Reported Light Output	39866 lm
Reported CCT	5000 K
Reported CRI (Ra)	82
Product ID	S-2ZNP4R
DLC Family Code	<u>JJJPCB</u>
Listing Status	Listed
Date Qualified	2022-08-17

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-2ZNP4R
Manufacturer	ESL Vision
Brand	ESL Vision
Model Number	ESL-MUR-280W-350
Parent	No
Classification	Standard
DLC Family Code	JJJPCB
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Retrofit Kit		
General Application	High-Bay		
Primary Use Designation	Retrofit Kits for High-Bay Luminaires for Commercial and Industrial Buildings		

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below

Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	39866 lm
Reported Efficacy (AC)	141.47 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	82
Reported R9	3
Reported IES Rf	82
Reported IES Rg	94
Reported IES Rcs,h1	-14
Reported Default Light Output	39866 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	281.8 W
Reported Total Harmonic Distortion	10 %
Reported Power Factor	0.939
Reported Default Input Wattage	281.8 W
Voltage Range	120-277 V

LISTING INFORMATION VIEW DETAILS

Testing in a Manufacturer-Selected Housing (Luminaire Specific)	General Purpose
--	-----------------

PHOTOMETRIC IMAGES AND FILES VIEW DETAILS

SPDX File	Download File
-----------	---------------

VERSION HISTORY VIEW DETAILS

2022-08-17	Listed	5.1	Standard