

# DesignLights Consortium



Classification	Standard
Primary Use	Retrofit Kits for High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	350.6 W
Reported Light Output	47941 lm
Reported CCT	5000 K
Reported CRI (Ra)	82
Product ID	S-WRXCPO
DLC Family Code	<a href="#">JJJPCB</a>
Listing Status	Listed
Date Qualified	2022-08-17

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-WRXCPO
Manufacturer	ESL Vision
Brand	ESL Vision
Model Number	ESL-MUR-350W-350
Parent	Yes
Classification	Standard
DLC Family Code	JJJPCB
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Retrofit Kit
General Application	High-Bay
Primary Use Designation	Retrofit Kits for High-Bay Luminaires for Commercial and Industrial Buildings

## CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below

Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	47941 lm
Reported Efficacy (AC)	136.74 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	82
Reported R9	2
Reported IES Rf	82
Reported IES Rg	94
Reported IES Rcs,h1	-14
Reported Default Light Output	47941 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	350.6 W
Reported Total Harmonic Distortion	9.3 %
Reported Power Factor	0.954
Reported Default Input Wattage	350.6 W
Voltage Range	120-277 V

## TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	47941 lm
Tested Efficacy (AC)	136.74 lm/W
Tested CCT	4922 K
Tested CRI (Ra)	82
Tested R9	2
Tested IES Rf	82
Tested IES Rg	94
Tested IES Rcs,h1	-14 %
Tested Duv	0.0037

## TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	350.6 W
Tested Total Harmonic Distortion	9.3 %
Tested Power Factor	0.954

## LISTING INFORMATION VIEW DETAILS

Testing in a Manufacturer-Selected Housing (Luminaire Specific)	General Purpose
---	-----------------

## PHOTOMETRIC IMAGES AND FILES VIEW DETAILS

SPDX File	<a href="#">Download File</a>
-----------	-------------------------------

## VERSION HISTORY VIEW DETAILS

2022-08-17	Listed	5.1	Standard
------------	--------	-----	----------