# DesignLights Consortium





Classification	Standard
Primary Use	Retrofit Kits for Fuel Pump Canopy Luminaires
Reported Input Wattage	73.3 W
Reported Light Output	9781 lm
Reported CCT	4000 K
Reported CRI (Ra)	84
Product ID	PVFXNJCG
DLC Family Code	HHHCWC
Listing Status	Listed
Date Qualified	2020-03-30

#### **PRODUCT INFORMATION VIEW DETAILS**

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PVFXNJCG
Manufacturer	ESL Vision
Brand	ESL Vision
Model Number	ESL-MUR-75W-340-HV
Parent	No
Classification	Standard
DLC Family Code	HHHCWC
Input Power Type	AC
Notes	Product Updated 7/27/2022

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Retrofit Kit
General Application	Mid Output
Primary Use Designation	Retrofit Kits for Fuel Pump Canopy Luminaires

#### **CONTROL FEATURES VIEW DETAILS**

Dimming Capability and Range	Continuous Dimming to 10% or below	
Integral Control Capability	No Control Capability	
Sensor Type	Exterior Photocell,Occupancy Sensing	
SSL V5 Wired Communication Protocol	0-10V Analog	
SSL V5 Wireless Communication Protocol	No Wireless Protocol	
Field Adjustable Light Output	No	
White-Tunable	No	
Warm-Dimming	No	
Field Adjustable Light Distribution	No	

#### **REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

Reported Light Output	9781 lm
Reported Efficacy (AC)	133.53 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	84
Reported R9	5
Reported IES Rf	84
Reported IES Rg	96
Reported IES Rcs,h1	-12
Reported Default Light Output	9781 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	73.3 W
Reported Total Harmonic Distortion	18.7 %
Reported Power Factor	0.894
Reported Default Input Wattage	73.3 W
Voltage Range	277-480 V

## LISTING INFORMATION VIEW DETAILS

Testing in a Manufacturer-Selected Housing (Luminaire Specific)	General Purpose
--	-----------------

#### VERSION HISTORY VIEW DETAILS

2022-07-27	Listed	5.1	Standard
2022-06-30	Delisted	5	Standard
2020-03-30	Listed	5	Standard
2018-11-02	Listed	4.4	Standard