# DesignLights Consortium





Classification	Standard
Primary Use	Internal Driver/Line Voltage (UL Type B) Lamps
Reported Input Wattage	9 W
Reported Light Output	1150 lm
Reported CCT	4000 K
Reported CRI (Ra)	82
Product ID	S-S29Y48
DLC Family Code	SSSEQY
Listing Status	Listed
Date Qualified	2022-11-21

## **PRODUCT INFORMATION VIEW DETAILS**

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-S29Y48
Manufacturer	Eiko Global, LLC
Brand	EiKO
Model Number	L9WT8/24/BSDG/840
Parent	No
Classification	Standard
DLC Family Code	SSSEQY
Length	2.0 ft
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Linear Replacement Lamp	
General Application	T8 Two-Foot	
Primary Use Designation Internal Driver/Line Voltage (UL Type B) Lamps		

#### **CONTROL FEATURES VIEW DETAILS**

Integral Controls	No

Dimming Capability and Range	Continuous Dimming above 10%		
Integral Control Capability	No Control Capability		
Sensor Type	No Sensor		
SSL V5 Wired Communication Protocol	Phase Cut, Other Wired Communication Protocol		
SSL V5 Wireless Communication Protocol	No Wireless Protocol		
Field Adjustable Light Output	No		
White-Tunable	No		
Warm-Dimming	No		
Field Adjustable Light Distribution	No		

## **REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

Reported Beam Angle	210 °
Reported Light Output	1150 lm
Reported Efficacy (AC)	128 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	82
Reported R9	0
Reported IES Rf	81
Reported IES Rg	94
Reported IES Rcs,h1	-13
Reported Default Light Output	1150 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	9 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Default Input Wattage	9 W
Voltage Range	120-277 V

### **VERSION HISTORY VIEW DETAILS**

2022-11-21	Listed	5.1	Standard
------------	--------	-----	----------