

# DesignLights Consortium



Classification	Premium
Primary Use	Outdoor Non-Cutoff and Semi-Cutoff Wall-Mounted Area Luminaires
Reported Input Wattage	28.7 W
Reported Light Output	3742 lm
Reported CCT	3000 K
Reported CRI (Ra)	84
Product ID	S-1TJCWL
DLC Family Code	<a href="#">QQQWAO</a>
Listing Status	Listed
Date Qualified	2023-06-28

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-1TJCWL
Manufacturer	Eiko Global, LLC
Brand	EiKO
Model Number	MWP1-PS30-FCCT-U-a-b-g
Parent	Yes
Classification	Premium
DLC Family Code	QQQWAO
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	Low Output
Primary Use Designation	Outdoor Non-Cutoff and Semi-Cutoff Wall-Mounted Area Luminaires

## CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Exterior Photocell
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	3742 lm
Reported Efficacy (AC)	130.29 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	84
Reported R9	14
Reported IES Rf	85
Reported IES Rg	99
Reported IES Rcs,h1	-10
Reported Minimum Light Output	1954 lm
Reported Maximum Light Output	3742 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	3742 lm
Reported BUG Rating	B1 U3 G2

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	28.7 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	15 W
Reported Maximum Input Wattage	28.7
Reported Default Input Wattage	28.7 W
Voltage Range	120-277 V

## TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	120
-------------------------------------	-----

Tested Light Output	3742 lm
Tested Efficacy (AC)	130.29 lm/W
Tested CCT	3080 K
Tested CRI (Ra)	84
Tested R9	14
Tested IES Rf	85
Tested IES Rg	99
Tested IES Rcs,h1	-10 %
Tested Duv	-0.0015
Tested Backlight (TM-15 BUG)	1
Tested BUG Rating	B1 U3 G2

## TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	28.7 W
Tested Total Harmonic Distortion	13.1 %
Tested Power Factor	0.931

## PHOTOMETRIC IMAGES AND FILES VIEW DETAILS

SPDX File	<a href="#">Download File</a>
-----------	-------------------------------

## VERSION HISTORY VIEW DETAILS

2023-06-28	Listed	5.1	Premium
------------	--------	-----	---------