DesignLights Consortium





| Classification | Standard | |
|------------------------|--|--|
| Primary Use | Internal Driver/Line Voltage (UL Type B) Lamps | |
| Reported Input Wattage | 7 W | |
| Reported Light Output | 950 lm | |
| Reported CCT | 3000 K | |
| Reported CRI (Ra) | 80 | |
| Product ID | S-5HKVPY | |
| DLC Family Code | <u>VVWAHS</u> | |
| Listing Status | Listed | |
| Date Qualified | 2023-06-26 | |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting |
|--------------------------------|----------------------|
| Technical Requirements Version | 5.1 |
| Product ID | S-5HKVPY |
| Manufacturer | Green Creative LTD |
| Brand | GREEN CREATIVE |
| Model Number | 7T8/2F/8CCTS/UEB |
| Parent | Yes |
| Classification | Standard |
| DLC Family Code | VVWAHS |
| Length | 2.0 ft |
| Input Power Type | AC |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Linear Replacement Lamp | |
|-------------------------|--|--|
| General Application | T8 Two-Foot | |
| Primary Use Designation | Internal Driver/Line Voltage (UL Type B) Lamps | |

CONTROL FEATURES VIEW DETAILS

| Integral Controls | No | |
|-------------------|----|--|
| | | |

| Dimming Capability and Range | Continuous Dimming to 10% or below |
|--|------------------------------------|
| Integral Control Capability | No Control Capability |
| Sensor Type | No Sensor |
| SSL V5 Wired Communication Protocol | Phase Cut |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol |
| Field Adjustable Light Output | No |
| White-Tunable | Yes |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | No |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Beam Angle | 160 ° |
|-------------------------------|----------|
| Reported Light Output | 950 lm |
| Reported Efficacy (AC) | 136 lm/W |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 80 |
| Reported R9 | 0 |
| Reported IES Rf | 79 |
| Reported IES Rg | 80 |
| Reported IES Rcs,h1 | -12 |
| Reported Minimum Light Output | 950 lm |
| Reported Maximum Light Output | 1030 lm |
| Reported Minimum CCT | 3000 K |
| Reported Maximum CCT | 6500 K |
| Reported Default Light Output | 950 lm |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 7 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 20 % |
| Reported Power Factor | 0.9 |
| Reported Maximum Input Wattage | 7 |
| Reported Default Input Wattage | 7 W |
| Voltage Range | 120-277 V |

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Tested Light Output | 1011 lm |
|----------------------|------------|
| Tested Efficacy (AC) | 144.5 lm/W |

| Tested CCT | 3040 K |
|-------------------|--------|
| Tested CRI (Ra) | 83 |
| Tested R9 | 9 |
| Tested IES Rf | 85 |
| Tested IES Rg | 94 |
| Tested IES Rcs,h1 | -11 % |
| Tested Duv | 0.0016 |

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Tested Voltage | 120 |
|----------------------------------|--------|
| Tested Input Wattage | 7 W |
| Tested Total Harmonic Distortion | 19.4 % |
| Tested Power Factor | 0.907 |

PHOTOMETRIC IMAGES AND FILES VIEW DETAILS

| SPDX File | Download File |
|-----------|---------------|
| | |

VERSION HISTORY VIEW DETAILS

| 023-06-26 | Listed | 5.1 | Standard |
|-----------|--------|-----|----------|
|-----------|--------|-----|----------|