DesignLights Consortium





| Classification | Standard | |
|------------------------|---|--|
| Primary Use | Replacement Lamps (Plug and Play) (UL Type A) | |
| Reported Input Wattage | 29 W | |
| Reported Light Output | 3450 lm | |
| Reported CCT | 3000 K | |
| Reported CRI (Ra) | 82 | |
| Product ID | P1QBZSCH | |
| DLC Family Code | LLLBEZ | |
| Listing Status | Listed | |
| Date Qualified | 2017-06-05 | |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting |
|--------------------------------|----------------------|
| Technical Requirements Version | 5.1 |
| Product ID | P1QBZSCH |
| Manufacturer | Green Creative LTD |
| Brand | Green Creative LTD |
| Model Number | 24T5HO/4F/830/DIR/R |
| Parent | Yes |
| Classification | Standard |
| DLC Family Code | LLLBEZ |
| Length | 4.0 ft |
| Input Power Type | AC |
| Notes | Updated 4/13/22 |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Linear Replacement Lamp |
|-------------------------|---|
| General Application | T5HO Four-Foot |
| Primary Use Designation | Replacement Lamps (Plug and Play) (UL Type A) |

CONTROL FEATURES VIEW DETAILS

| Integral Controls | No |
|--|------------------------------------|
| Dimming Capability and Range | Continuous Dimming to 10% or below |
| Integral Control Capability | No Control Capability |
| Sensor Type | No Sensor |
| SSL V5 Wired Communication Protocol | Other Wired Communication Protocol |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol |
| Field Adjustable Light Output | No |
| White-Tunable | No |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | No |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Beam Angle | 140 ° |
|-------------------------------|----------|
| Reported Light Output | 3450 lm |
| Reported Efficacy (AC) | 119 lm/W |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 82 |
| Reported R9 | 0 |
| Reported IES Rf | 85 |
| Reported IES Rg | 96 |
| Reported IES Rcs,h1 | -12 |
| Reported Default Light Output | 3450 lm |
| | |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 29 W |
|------------------------------------|------|
| Reported Total Harmonic Distortion | 20 % |
| Reported Power Factor | 0.9 |
| Reported Default Input Wattage | 29 W |

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Tested Voltage for Minimum Efficacy | 120 |
|-------------------------------------|------------|
| Tested Light Output | 3433 lm |
| Tested Efficacy (AC) | 118.6 lm/W |
| Tested CCT | 3041 K |
| Tested CRI (Ra) | 82 |
| Tested R9 | 4 |
| Tested IES Rf | 85 |

| Tested IES Rg | 96 |
|-------------------|--------|
| Tested IES Rcs,h1 | -12 % |
| Tested Duv | 0.0001 |
| Tested Beam Angle | 137 ° |

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Tested Input Wattage | 29 W |
|----------------------------------|--------|
| Tested Total Harmonic Distortion | 12.4 % |
| Tested Power Factor | 0.964 |

VERSION HISTORY VIEW DETAILS

| 2022-04-13 | Listed | 5.1 | Standard |
|------------|--------|-----|----------|
| 2020-03-30 | Listed | 5 | Standard |
| 2018-11-02 | Listed | 4.4 | Standard |
| 2018-06-04 | Listed | 4.3 | Standard |
| 2018-05-02 | Listed | 4.3 | Standard |
| 2017-06-05 | Listed | 4.2 | Standard |