DesignLights Consortium





Classification	Premium
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	154.88 W
Reported Light Output	22163.8 lm
Reported CCT	4000 K
Reported CRI (Ra)	80
Product ID	P30HF6DM
DLC Family Code	BBBFUO
Listing Status	Listed
Date Qualified	2021-09-07

PRODUCT INFORMATION VIEW DETAILS

Solid State Lighting
5.1
P30HF6DM
Halco Lighting Technologies
Halco
HRHB-150-CS-U-abc
No
Premium
BBBFUO
AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires	
General Application	High-Bay	
Primary Use Designation	High-Bay Luminaires for Commercial and Industrial Buildings	

CONTROL FEATURES VIEW DETAILS

Integral Controls

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	Yes
Field Adjustable Distribution Type	Integral FALD

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	22163.8 lm
Reported Efficacy (AC)	143.1 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	80
Reported R9	12
Reported IES Rf	84
Reported IES Rg	97
Reported IES Rcs,h1	-11
Reported Minimum CCT	4000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	22163.8 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	154.88 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	150 W
Reported Maximum Input Wattage	154.88
Reported Default Input Wattage	150 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Field Adjustable Light Distribution Setting

Pointing straight down

VERSION HISTORY VIEW DETAILS

2021-09-07	Listed	5.1	Premium
2021-09-06	Listed	5.1	Premium