DesignLights Consortium





Classification	Premium
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	160 W
Reported Light Output	21600 lm
Reported CCT	5000 K
Reported CRI (Ra)	80
Product ID	PLGFVWVKC19G
DLC Family Code	LLLCBT
Listing Status	Listed
Date Qualified	2021-12-10

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PLGFVWVKC19G
Manufacturer	Halco Lighting Technologies
Brand	HALCO
Model Number	LHB-2-WS-50-U-[Blank,EM]-[Blank,LVMS,PIRMS]
Parent	No
Classification	Premium
DLC Family Code	LLLCBT
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires	
General Application	High-Bay	
Primary Use Designation High-Bay Luminaires for Commercial and Industrial Buildings		

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	21600 lm
Reported Efficacy (AC)	135 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	80
Reported R9	-6
Reported IES Rf	82
Reported IES Rg	92
Reported IES Rcs,h1	-14
Reported Minimum Light Output	15400 lm
Reported Maximum Light Output	21600 lm
Reported Default Light Output	21600 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	160 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	110 W
Reported Default Input Wattage	160 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

	2021-12-10	Listed	5.1	Premium
--	------------	--------	-----	---------