DesignLights Consortium





Classification	Premium
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	220 W
Reported Light Output	29634 lm
Reported CCT	4000 K
Reported CRI (Ra)	80
Product ID	PL4CV2L4KR0L
DLC Family Code	LLLCBT
Listing Status	Listed
Date Qualified	2021-12-10

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PL4CV2L4KR0L
Manufacturer	Halco Lighting Technologies
Brand	HALCO
Model Number	LHB-3-WS-40-U-[Blank,EM]-[Blank,LVMS,PIRMS]
Parent	Yes
Classification	Premium
DLC Family Code	LLLCBT
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires	
General Application	High-Bay	
Primary Use Designation High-Bay Luminaires for Commercial and Industrial Buildings		

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range Integral Control Capability No Control Capability Sensor Type Occupancy Sensing SSL V5 Wired Communication Protocol SSL V5 Wireless Communication Protocol No Wireless Protocol Field Adjustable Light Output Yes White-Tunable No Warm-Dimming No Field Adjustable Light Distribution No		
Sensor Type Occupancy Sensing SSL V5 Wired Communication Protocol 0-10V Analog SSL V5 Wireless Communication Protocol No Wireless Protocol Field Adjustable Light Output Yes White-Tunable No Warm-Dimming No	Dimming Capability and Range	Continuous Dimming to 10% or below
SSL V5 Wired Communication Protocol SSL V5 Wireless Communication Protocol Field Adjustable Light Output Yes White-Tunable No Warm-Dimming No	Integral Control Capability	No Control Capability
SSL V5 Wireless Communication Protocol Field Adjustable Light Output Yes White-Tunable No Warm-Dimming No	Sensor Type	Occupancy Sensing
Field Adjustable Light Output White-Tunable Warm-Dimming No	SSL V5 Wired Communication Protocol	0-10V Analog
White-Tunable No Warm-Dimming No	SSL V5 Wireless Communication Protocol	No Wireless Protocol
Warm-Dimming No	Field Adjustable Light Output	Yes
J	White-Tunable	No
Field Adjustable Light Distribution No	Warm-Dimming	No
	Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	29634 lm
Reported Efficacy (AC)	134.7 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	80
Reported R9	10
Reported IES Rf	83
Reported IES Rg	97
Reported IES Rcs,h1	-12
Reported Minimum Light Output	24840 lm
Reported Maximum Light Output	29634 lm
Reported Default Light Output	29634 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	220 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	180 W
Reported Default Input Wattage	220 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	30672 lm
Tested Efficacy (AC)	135 lm/W

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
----------------	-----

Tested Input Wattage	228 W

VERSION HISTORY VIEW DETAILS

2021-12-10	Listed	5.1	Premium
------------	--------	-----	---------