

DesignLights Consortium



| | |
|------------------------|-------------------------------------|
| Classification | Premium |
| Primary Use | Stairwell and Passageway Luminaires |
| Reported Input Wattage | 59.1 W |
| Reported Light Output | 7551 lm |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 70 |
| Product ID | S-VTAN8X |
| DLC Family Code | QQQVXS |
| Listing Status | Listed |
| Date Qualified | 2022-12-19 |

PRODUCT INFORMATION VIEW DETAILS

| | |
|--------------------------------|-----------------------------|
| Qualified Product List | Solid State Lighting |
| Technical Requirements Version | 5.1 |
| Product ID | S-VTAN8X |
| Manufacturer | Halco Lighting Technologies |
| Brand | ProLED |
| Model Number | CSP-60-CS-U-XX-YY |
| Parent | No |
| Classification | Premium |
| DLC Family Code | QQQVXS |
| Input Power Type | AC |

PRODUCT CATEGORIZATION VIEW DETAILS

| | |
|-------------------------|-------------------------------------|
| Category | Outdoor Luminaires |
| General Application | Mid Output |
| Primary Use Designation | Stairwell and Passageway Luminaires |

CONTROL FEATURES VIEW DETAILS

| | |
|-------------------|-----|
| Integral Controls | Yes |
|-------------------|-----|

| | |
|--|--------------------------------------|
| Dimming Capability and Range | Continuous Dimming to 10% or below |
| Integral Control Capability | No Control Capability |
| Sensor Type | Exterior Photocell,Occupancy Sensing |
| SSL V5 Wired Communication Protocol | 0-10V Analog |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol |
| Field Adjustable Light Output | Yes |
| White-Tunable | Yes |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | No |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| | |
|-------------------------------|----------|
| Reported Light Output | 7551 lm |
| Reported Efficacy (AC) | 128 lm/W |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 70 |
| Reported R9 | -33 |
| Reported IES Rf | 75 |
| Reported IES Rg | 92 |
| Reported IES Rcs,h1 | -17 |
| Reported Minimum Light Output | 3640 lm |
| Reported Maximum Light Output | 7551 lm |
| Reported Minimum CCT | 3000.0 K |
| Reported Maximum CCT | 5000.0 K |
| Reported Default Light Output | 7551 lm |
| Reported BUG Rating | B3 U3 G2 |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| | |
|------------------------------------|-----------|
| Reported Input Wattage | 59.1 W |
| Reported Total Harmonic Distortion | 9.2 % |
| Reported Power Factor | 0.9 |
| Reported Minimum Input Wattage | 56.3 W |
| Reported Maximum Input Wattage | 59.1 |
| Reported Default Input Wattage | 59.1 W |
| Voltage Range | 120-347 V |

PHOTOMETRIC IMAGES AND FILES VIEW DETAILS

| | |
|-----------|-------------------------------|
| SPDX File | Download File |
|-----------|-------------------------------|

VERSION HISTORY VIEW DETAILS

| | | | |
|------------|--------|-----|---------|
| 2022-12-19 | Listed | 5.1 | Premium |
|------------|--------|-----|---------|