DesignLights Consortium





Classification	Standard	
Primary Use	Internal Driver/Line Voltage (UL Type B) Lamps	
Reported Input Wattage	17 W	
Reported Light Output	2150 lm	
Reported CCT	3500 K	
Reported CRI (Ra)	82	
Product ID	PLYTFBWQ6BA6	
DLC Family Code	CCCHFM	
Listing Status	Listed	
Date Qualified	2021-01-07	

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PLYTFBWQ6BA6
Manufacturer	Halco Lighting Technologies
Brand	Halco ProLED
Model Number	PLL17-835-BYP-LED
Parent	No
Classification	Standard
DLC Family Code	CCCHFM
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Four Pin-Base Replacement Lamps for CFLs	
General Application	2G11 Base Replacement Lamps	
Primary Use Designation	Internal Driver/Line Voltage (UL Type B) Lamps	

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below

Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	Other Wired Communication Protocol
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Beam Angle	140 °
Reported Light Output	2150 lm
Reported Efficacy (AC)	126 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	82
Reported R9	0
Reported IES Rf	85
Reported IES Rg	97
Reported IES Rcs,h1	-11
Reported Default Light Output	2150 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	17 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Default Input Wattage	17 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2022-06-09	Listed	5.1	Standard
2021-01-07	Listed	5	Standard