DesignLights Consortium





Classification	Standard
Primary Use	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces
Reported Input Wattage	45 W
Reported Light Output	5535 lm
Reported CCT	3500 K
Reported CRI (Ra)	83
Product ID	PMM73646
DLC Family Code	DDDLOQ
Listing Status	Listed
Date Qualified	2021-09-02

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PMM73646
Manufacturer	Keystone Technologies
Brand	Keystone
Model Number	KT-CBLED45PS-24B-8CSA-VDIM [blank, -Options]
Parent	No
Classification	Standard
DLC Family Code	DDDLOQ
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires		
General Application	Troffer		
Primary Use Designation	2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces		

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes	
Dimming Capability and Range	Continuous Dimming to 10% or below	

Integral Control Capability	No Control Capability		
Sensor Type	Daylight Sensing, Occupancy Sensing		
SSL V5 Wired Communication Protocol	0-10V Analog		
SSL V5 Wireless Communication Protocol	Bluetooth		
Field Adjustable Light Output	Yes		
White-Tunable	Yes		
Warm-Dimming	No		
Field Adjustable Light Distribution	No		

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	5535 lm
Reported Efficacy (AC)	123 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	83
Reported R9	8
Reported IES Rf	84
Reported IES Rg	95
Reported IES Rcs,h1	-12
Reported Minimum Light Output	3690 lm
Reported Maximum Light Output	5625 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	5535 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	45 W
Reported Total Harmonic Distortion	7.25 %
Reported Power Factor	0.9949
Reported Minimum Input Wattage	30 W
Reported Maximum Input Wattage	45
Reported Default Input Wattage	45 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2023-03-14	Listed	5.1	Standard
2021-09-02	Listed	5.1	Standard
2021-09-01	Listed	5.1	Standard