

DesignLights Consortium



Classification	Standard
Primary Use	Architectural Flood and Spot Luminaires
Reported Input Wattage	15 W
Reported Light Output	1650 lm
Reported CCT	3000 K
Reported CRI (Ra)	80
Product ID	S-PG1Q8Z
DLC Family Code	EEEEGTR
Listing Status	Listed
Date Qualified	2022-12-28

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-PG1Q8Z
Manufacturer	Keystone Technologies
Brand	KEYSTONE
Model Number	KT-FLED15-R3A-KM-830-[Blank or X or Y or Z]
Parent	No
Classification	Standard
DLC Family Code	EEEEGTR
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	Low Output
Primary Use Designation	Architectural Flood and Spot Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming above 10%

Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	Phase Cut
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	Yes
Field Adjustable Distribution Type	Integral FALD

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	1650 lm
Reported Efficacy (AC)	110 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	80
Reported R9	6
Reported IES Rf	83
Reported IES Rg	97
Reported IES Rcs,h1	-12
Reported Default Light Output	1650 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	15 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Maximum Input Wattage	15
Reported Default Input Wattage	15 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Field Adjustable Light Distribution Setting	Straight Down
---	---------------

VERSION HISTORY VIEW DETAILS

2022-12-28	Listed	5.1	Standard
------------	--------	-----	----------