DesignLights Consortium





Classification	Standard
Primary Use	Internal Driver/Line Voltage (UL Type B) Lamps
Reported Input Wattage	12 W
Reported Light Output	1800 lm
Reported CCT	3000 K
Reported CRI (Ra)	80
Product ID	S-ZY34HA
DLC Family Code	SSSENF
Listing Status	Listed
Date Qualified	2022-07-01

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-ZY34HA
Manufacturer	Keystone Technologies
Brand	Keystone
Model Number	KT-LED12T8-48G-8CSJ-DX2
Parent	No
Classification	Standard
DLC Family Code	SSSENF
Length	4.0 ft
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Linear Replacement Lamp	
General Application	T8 Four-Foot	
Primary Use Designation	Internal Driver/Line Voltage (UL Type B) Lamps	

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
-------------------	----

Dimming Capability and Range	Continuous Dimming to 10% or below	
Integral Control Capability	No Control Capability	
Sensor Type	No Sensor	
SSL V5 Wired Communication Protocol	Phase Cut	
SSL V5 Wireless Communication Protocol	No Wireless Protocol	
Field Adjustable Light Output	No	
White-Tunable	Yes	
Warm-Dimming	No	
Field Adjustable Light Distribution	No	

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Beam Angle	180 °
Reported Light Output	1800 lm
Reported Efficacy (AC)	150 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	80
Reported R9	0
Reported IES Rf	70
Reported IES Rg	89
Reported IES Rcs,h1	-11
Reported Minimum CCT	3000 K
Reported Maximum CCT	6500 K
Reported Default Light Output	1800 lm
Reported Minimum CCT Reported Maximum CCT	3000 K 6500 K

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	12 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Default Input Wattage	12 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2022-07-08	Listed	5.1	Standard
2022-07-01	Listed	5.1	Standard