

DesignLights Consortium



Classification	Standard
Primary Use	Replacement Lamps for Outdoor Pole/Arm-Mounted Decorative Luminaires (Type B)
Reported Input Wattage	36 W
Reported Light Output	4021.1 lm
Reported CCT	3000 K
Reported CRI (Ra)	83.1
Product ID	PW4W6Z3T
DLC Family Code	BBBFNK
Listing Status	Listed
Date Qualified	2020-10-01

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PW4W6Z3T
Manufacturer	Keystone Technologies
Brand	Keystone
Model Number	KT-LED36PSHID-EX39-8CSB-D [blank, /PIR, /MW, /PS]
Parent	Yes
Classification	Standard
DLC Family Code	BBBFNK
Length	0.7 ft
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Mogul (E39) Screw-Base Replacements for HID Lamps
General Application	Low Output
Primary Use Designation	Replacement Lamps for Outdoor Pole/Arm-Mounted Decorative Luminaires (Type B)

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Sensor Type	Integral Sensor Receptacle
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	4021.1 lm
Reported Efficacy (AC)	112 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	83.1
Reported R9	12
Reported IES Rf	84
Reported IES Rg	94
Reported IES Rcs,h1	-11
Reported Minimum Light Output	2028.6 lm
Reported Maximum Light Output	4154.3 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	4021.1 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	36 W
Reported Total Harmonic Distortion	13.1 %
Reported Power Factor	0.916
Reported Minimum Input Wattage	18 W
Reported Maximum Input Wattage	36
Reported Default Input Wattage	35.6 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	4021.17 lm
Tested Efficacy (AC)	112.7 lm/W

Tested CCT	3100 K
Tested CRI (Ra)	83
Tested R9	12
Tested IES Rf	84
Tested IES Rg	94
Tested IES Rcs,h1	-11 %
Tested Duv	0.0006

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	35.68 W
Tested Total Harmonic Distortion	13.1 %
Tested Power Factor	0.916

VERSION HISTORY VIEW DETAILS

2021-03-05	Listed	5.1	Standard
2020-10-01	Listed	5.1	Standard