DesignLights Consortium





| Classification | Standard |
|------------------------|-------------------------------------------------------------------------------|
| Primary Use | Replacement Lamps for Outdoor Pole/Arm-Mounted Decorative Luminaires (Type B) |
| Reported Input Wattage | 61.4 W |
| Reported Light Output | 6566 lm |
| Reported CCT | 4000 K |
| Reported CRI (Ra) | 84 |
| Product ID | PLLNUOKRPBX3 |
| DLC Family Code | <u> </u> |
| Listing Status | Listed |
| Date Qualified | 2019-08-01 |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting |
|--------------------------------|----------------------------------------------------|
| Technical Requirements Version | 5.1 |
| Product ID | PLLNUOKRPBX3 |
| Manufacturer | Keystone Technologies |
| Brand | Keystone |
| Model Number | KT-LED63HID-EX39-840-D /G3 [blank, /PIR, /MW, /PS] |
| Parent | No |
| Classification | Standard |
| DLC Family Code | JJJONI |
| Length | 0.9 ft |
| Input Power Type | AC |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Mogul (E39) Screw-Base Replacements for HID Lamps | |
|-------------------------|-------------------------------------------------------------------------------|--|
| General Application | Mid Output | |
| Primary Use Designation | Replacement Lamps for Outdoor Pole/Arm-Mounted Decorative Luminaires (Type B) | |

CONTROL FEATURES VIEW DETAILS

| 1.0.10 | N |
|-------------------|----|
| Integral Controls | No |

| Dimming Capability and Range | Stepped Dimmable |
|----------------------------------------|----------------------|
| Sensor Type | No Sensor |
| SSL V5 Wired Communication Protocol | 0-10V Analog |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol |
| Field Adjustable Light Output | No |
| White-Tunable | No |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | No |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output | 6566 lm |
|-------------------------------|------------|
| Reported Efficacy (AC) | 106.8 lm/W |
| Reported CCT | 4000 K |
| Reported CRI (Ra) | 84 |
| Reported R9 | 15 |
| Reported IES Rf | 85 |
| Reported IES Rg | 94 |
| Reported IES Rcs,h1 | -11 |
| Reported Default Light Output | 6566 lm |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 61.4 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 14 % |
| Reported Power Factor | 0.918 |
| Reported Default Input Wattage | 61.4 W |
| Voltage Range | 120-277 V |

VERSION HISTORY VIEW DETAILS

| 2021-03-04 | Listed | 5.1 | Standard |
|------------|--------|-----|----------|
| 2020-03-30 | Listed | 5 | Standard |
| 2019-08-01 | Listed | 4.4 | Standard |