DesignLights Consortium







| Model Number | KT-LED7T8-24GC-840-DX2 /G2 |
|------------------------|--|
| Classification | Standard |
| Primary Use | Internal Driver/Line Voltage (UL Type B) Lamps |
| Reported Input Wattage | 7 W |
| Reported Light Output | 1000 lm |
| Reported CCT | 4000 K |
| Reported CRI (Ra) | 82 |
| Product ID | S-TC4ANP |
| DLC Family Code | XXXEYP |
| Listing Status | Listed |
| Date Qualified | 2023-07-12 |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting | | |
|--------------------------------|----------------------------|--|--|
| Technical Requirements Version | 5.1 | | |
| Product ID | S-TC4ANP | | |
| Manufacturer | Keystone Technologies | | |
| Brand | Keystone | | |
| Model Number | KT-LED7T8-24GC-840-DX2 /G2 | | |
| Parent | No | | |
| Classification | Standard | | |
| DLC Family Code | XXXEYP | | |
| Length | 2.0 ft | | |
| Input Power Type | AC | | |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Linear Replacement Lamp | |
|-------------------------|--|--|
| General Application | T8 Two-Foot | |
| Primary Use Designation | Internal Driver/Line Voltage (UL Type B) Lamps | |

CONTROL FEATURES VIEW DETAILS

| Integral Controls | No | | |
|--|------------------------------------|--|--|
| Dimming Capability and Range | Continuous Dimming above 10% | | |
| Integral Control Capability | No Control Capability | | |
| Sensor Type | No Sensor | | |
| SSL V5 Wired Communication Protocol | Other Wired Communication Protocol | | |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol | | |
| Field Adjustable Light Output | No | | |
| White-Tunable | No | | |
| Warm-Dimming | No | | |
| Field Adjustable Light Distribution | No | | |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Beam Angle | 170 ° |
|-------------------------------|----------|
| Reported Light Output | 1000 lm |
| Reported Efficacy (AC) | 143 lm/W |
| Reported CCT | 4000 K |
| Reported CRI (Ra) | 82 |
| Reported R9 | 0 |
| Reported IES Rf | 70 |
| Reported IES Rg | 89 |
| Reported IES Rcs,h1 | -12 |
| Reported Default Light Output | 1000 lm |
| | |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 7 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 20 % |
| Reported Power Factor | 0.9 |
| Reported Default Input Wattage | 7 W |
| Voltage Range | 120-277 V |

VERSION HISTORY VIEW DETAILS

| 3-09-21 | Listed | 5.1 | Standard |
|---------|--------|-----|----------|
|---------|--------|-----|----------|