

DesignLights Consortium



Model Number	KT-LED94P-H-8CSE-S
Classification	Standard
Primary Use	Replacement Lamps (Plug and Play) (UL Type A)
Reported Input Wattage	11.5 W
Reported Light Output	1050 lm
Reported CCT	3000 K
Reported CRI (Ra)	82
Product ID	PL8A9VJ9A3G7
DLC Family Code	SSSEKD
Listing Status	Listed
Date Qualified	2021-11-08

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PL8A9VJ9A3G7
Manufacturer	Keystone Technologies
Brand	Keystone
Model Number	KT-LED94P-H-8CSE-S
Parent	Yes
Classification	Standard
DLC Family Code	SSSEKD
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Four Pin-Base Replacement Lamps for CFLs
General Application	Horizontally-Mounted Lamps
Primary Use Designation	Replacement Lamps (Plug and Play) (UL Type A)

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
-------------------	----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	Other Wired Communication Protocol
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	1050 lm
Reported Efficacy (AC)	91.3 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	82
Reported R9	3
Reported IES Rf	80
Reported IES Rg	90
Reported IES Rcs,h1	-12
Reported Minimum Light Output	1050 lm
Reported Maximum Light Output	1050 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	4000 K
Reported Default Light Output	1050 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	11.5 W
Reported Total Harmonic Distortion	10 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	11.5 W
Reported Maximum Input Wattage	11.5
Reported Default Input Wattage	11.5 W

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Voltage for Minimum Efficacy	277
Tested Light Output	1092.7 lm
Tested Efficacy (AC)	101.9 lm/W

Tested CCT	3020 K
Tested CRI (Ra)	82
Tested R9	6
Tested IES Rf	84
Tested IES Rg	96
Tested IES Rcs,h1	-12 %
Tested Duv	-0.0022

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	10.72 W
Tested Total Harmonic Distortion	8.78 %
Tested Power Factor	0.9794

VERSION HISTORY VIEW DETAILS

2021-11-08	Listed	5.1	Standard
------------	--------	-----	----------