

DesignLights Consortium



Classification	Standard
Primary Use	Direct Linear Ambient Luminaires
Reported Input Wattage	44 W
Reported Light Output	5808 lm
Reported CCT	3500 K
Reported CRI (Ra)	80
Product ID	PFPBU4KQ
DLC Family Code	FFFJZW
Listing Status	Listed
Date Qualified	2021-10-12

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PFPBU4KQ
Manufacturer	Keystone Technologies
Brand	Keystone
Model Number	KT-MSLED44PS-4-8CSA-VDIM [Blank, Options]
Parent	Yes
Classification	Standard
DLC Family Code	FFFJZW
Length	4.0 ft
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	Linear Ambient
Primary Use Designation	Direct Linear Ambient Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	LLLC,High End Trim
Sensor Type	Multifunction Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	Bluetooth
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	5808 lm
Reported Efficacy (AC)	132 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	80
Reported R9	6
Reported IES Rf	83
Reported IES Rg	94
Reported IES Rcs,h1	-12
Reported Minimum Light Output	2556 lm
Reported Maximum Light Output	5896 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	5896 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	44 W
Reported Total Harmonic Distortion	3.6 %
Reported Power Factor	0.993
Reported Minimum Input Wattage	18 W
Reported Maximum Input Wattage	44
Reported Default Input Wattage	44 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	5993 lm
Tested Efficacy (AC)	130.93 lm/W

Tested CCT	3400 K
Tested CRI (Ra)	83
Tested R9	6
Tested IES Rf	84
Tested IES Rg	94
Tested IES Rcs,h1	-12 %
Tested Duv	0.0014

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	45.8 W
Tested Total Harmonic Distortion	4.9 %
Tested Power Factor	0.982

VERSION HISTORY VIEW DETAILS

2023-04-07	Listed	5.1	Standard
2023-02-17	Listed	5.1	Standard
2021-10-12	Listed	5.1	Standard