# **DesignLights Consortium**





Classification	Standard
Primary Use	Retrofit Kits for Direct Linear Ambient Luminaires
Reported Input Wattage	32 W
Reported Light Output	4096 lm
Reported CCT	3500 K
Reported CRI (Ra)	83
Product ID	PO2S8UHT
DLC Family Code	RRRWGS
Listing Status	Listed
Date Qualified	2021-10-04

## **PRODUCT INFORMATION VIEW DETAILS**

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PO2S8UHT
Manufacturer	Keystone Technologies
Brand	Keystone
Model Number	KT-RKIT32PS-4S-8CSA-VDIM
Parent	No
Classification	Standard
DLC Family Code	RRRWGS
Length	4.0 ft
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Retrofit Kit
General Application	Linear Ambient
Primary Use Designation	Retrofit Kits for Direct Linear Ambient Luminaires

## **CONTROL FEATURES VIEW DETAILS**

trols No
----------

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

#### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

4096 lm
128 lm/W
3500 K
83
9
83
96
-12
2304 lm
4160 lm
3500 K
5000 K
4096 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	32 W
Reported Total Harmonic Distortion	2.85 %
Reported Power Factor	0.9931
Reported Minimum Input Wattage	18 W
Reported Maximum Input Wattage	32
Reported Default Input Wattage	32 W
Voltage Range	120-277 V

## LISTING INFORMATION VIEW DETAILS

Testing in a Manufacturer-Selected Housing (Luminaire Specific)	General Purpose
--	-----------------

## **VERSION HISTORY VIEW DETAILS**

2021-10-04 Listed 5.1 Stand	andard
-----------------------------	--------