

DesignLights Consortium



Classification	Standard
Primary Use	Integrated Retrofit Kits for 1x4 Luminaires
Reported Input Wattage	40 W
Reported Light Output	4400 lm
Reported CCT	3500 K
Reported CRI (Ra)	84
Product ID	PHUSXCLW
DLC Family Code	BBBFPJ
Listing Status	Listed
Date Qualified	2020-12-30

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PHUSXCLW
Manufacturer	Keystone Technologies
Brand	Keystone
Model Number	KT-RKIT40PS-14PD-8CSA-VDIM [blank, /FC1-PIR]
Parent	Yes
Classification	Standard
DLC Family Code	BBBFPJ
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Retrofit Kit
General Application	Troffer
Primary Use Designation	Integrated Retrofit Kits for 1x4 Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below

Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	4400 lm
Reported Efficacy (AC)	110 lm/W
Reported CCT	3500 K
Reported CRI (Ra)	84
Reported R9	14.5
Reported IES Rf	85
Reported IES Rg	98
Reported IES Rcs,h1	-11
Reported Minimum Light Output	2200 lm
Reported Maximum Light Output	4500 lm
Reported Minimum CCT	3500 K
Reported Maximum CCT	5000 K
Reported Default Light Output	4500 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	40 W
Reported Total Harmonic Distortion	7.15 %
Reported Power Factor	0.9971
Reported Minimum Input Wattage	20 W
Reported Maximum Input Wattage	40
Reported Default Input Wattage	40 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	4482.2 lm
Tested Efficacy (AC)	109.3 lm/W
Tested CCT	3456 K
Tested CRI (Ra)	84

Tested R9	15
Tested IES Rf	85
Tested IES Rg	98
Tested IES Rcs,h1	-11 %
Tested Duv	-0.0016

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	41 W
Tested Total Harmonic Distortion	7.27 %
Tested Power Factor	0.9679

LISTING INFORMATION VIEW DETAILS

Testing in a Manufacturer-Selected Housing (Luminaire Specific)	General Purpose
---	-----------------

VERSION HISTORY VIEW DETAILS

2021-05-14	Listed	5.1	Standard
2020-12-30	Listed	5.1	Standard