DesignLights Consortium





Classification	Premium
Primary Use	Outdoor Full-Cutoff Wall-Mounted Area Luminaires
Reported Input Wattage	60 W
Reported Light Output	7500 lm
Reported CCT	4000 K
Reported CRI (Ra)	83.4
Product ID	PIKA3HFT
DLC Family Code	RRRVXF
Listing Status	Listed
Date Qualified	2020-08-10

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting		
Technical Requirements Version	5.1		
Product ID	PIKA3HFT		
Manufacturer	Keystone Technologies		
Brand	Keystone		
Model Number	KT-WPLED60-M2-840-VDIM-[blank, B, W] [blank, /MW]		
Parent	No		
Classification	Premium		
DLC Family Code	RRRVXF		
Input Power Type	AC		

PRODUCT CATEGORIZATION VIEW DETAILS

Category Outdoor Luminaires	
General Application	Mid Output
imary Use Designation Outdoor Full-Cutoff Wall-Mounted Area Luminaires	

CONTROL FEATURES VIEW DETAILS

Integral Controls Yes

Dimming Capability and Range	Continuous Dimming to 10% or below	
Integral Control Capability	No Control Capability	
Sensor Type	Occupancy sensing	
SSL V5 Wired Communication Protocol	0-10V Analog	
SSL V5 Wireless Communication Protocol	No Wireless Protocol	
Field Adjustable Light Output	No	
White-Tunable	No	
Warm-Dimming	No	
Field Adjustable Light Distribution	No	

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	7500 lm
Reported Efficacy (AC)	125 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	83.4
Reported R9	11
Reported IES Rf	84
Reported IES Rg	95
Reported IES Rcs,h1	-12
Reported Default Light Output	7500 lm
Reported BUG Rating	B2 U2 G2

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	60 W
Reported Total Harmonic Distortion	10.21 %
Reported Power Factor	0.994
Reported Default Input Wattage	60 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2021-04-23	Listed	5.1	Premium
2021-02-12	Listed	5	Premium
2020-08-10	Listed	5	Premium