

# DesignLights Consortium



Classification	Standard
Primary Use	Replacement Lamps for High-Bay Luminaires (Type B)
Reported Input Wattage	132.8 W
Reported Light Output	19347 lm
Reported CCT	4000 K
Reported CRI (Ra)	84
Product ID	S-THOIWL
DLC Family Code	<a href="#">RRRXIY</a>
Listing Status	Listed
Date Qualified	2023-01-04

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-THOIWL
Manufacturer	Light Efficient Design
Brand	LIGHT EFFICIENT DESIGN
Model Number	LED-8132M40D
Parent	No
Classification	Standard
DLC Family Code	RRRXIY
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Mogul (E39) Screw-Base Replacements for HID Lamps
General Application	High-Bay
Primary Use Designation	Replacement Lamps for High-Bay Luminaires (Type B)

## CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below

Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	19347 lm
Reported Efficacy (AC)	145.69 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	84
Reported R9	12
Reported IES Rf	85
Reported IES Rg	97
Reported IES Rcs,h1	-11
Reported Default Light Output	19347 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	132.8 W
Reported Total Harmonic Distortion	19.6 %
Reported Power Factor	0.876
Reported Default Input Wattage	132.8 W
Voltage Range	120-277 V

## VERSION HISTORY VIEW DETAILS

2023-01-04	Listed	5.1	Standard
------------	--------	-----	----------