DesignLights Consortium





Classification	Premium
Primary Use	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires
Reported Input Wattage	301.8 W
Reported Light Output	38641 lm
Reported CCT	3000 K
Reported CRI (Ra)	82
Product ID	S-NFUT4E
DLC Family Code	BBBGII
Listing Status	Listed
Date Qualified	2023-06-05

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-NFUT4E
Manufacturer	Litetronics International
Brand	Litetronics
Model Number	AL3003
Parent	No
Classification	Premium
DLC Family Code	BBBGII
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	Very High Output
Primary Use Designation	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range Integral Control Capability Sensor Type Sensor Receptacle SSL V5 Wired Communication Protocol SSL V5 Wireless Communication Protocol Field Adjustable Light Output White-Tunable Warm-Dimming No Field Adjustable Light Distribution No		
Sensor Type Sensor Receptacle SSL V5 Wired Communication Protocol 0-10V Analog SSL V5 Wireless Communication Protocol No Wireless Protocol Field Adjustable Light Output Yes White-Tunable Yes Warm-Dimming No	Dimming Capability and Range	Continuous Dimming to 10% or below
SSL V5 Wired Communication Protocol SSL V5 Wireless Communication Protocol Field Adjustable Light Output White-Tunable Warm-Dimming No	Integral Control Capability	No Control Capability
SSL V5 Wireless Communication Protocol Field Adjustable Light Output White-Tunable Warm-Dimming No	Sensor Type	Sensor Receptacle
Field Adjustable Light Output White-Tunable Warm-Dimming No	SSL V5 Wired Communication Protocol	0-10V Analog
White-Tunable Yes Warm-Dimming No	SSL V5 Wireless Communication Protocol	No Wireless Protocol
Warm-Dimming No	Field Adjustable Light Output	Yes
5	White-Tunable	Yes
Field Adjustable Light Distribution No	Warm-Dimming	No
	Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	38641 lm
Reported Efficacy (AC)	128 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	82
Reported R9	3
Reported IES Rf	84
Reported IES Rg	96
Reported IES Rcs,h1	-12
Reported Minimum Light Output	32400 lm
Reported Maximum Light Output	40500 lm
Reported Minimum CCT	3000.0 K
Reported Maximum CCT	5000.0 K
Reported Default Light Output	38641 lm
Reported BUG Rating	B5 U0 G5

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	301.8 W
Reported Total Harmonic Distortion	8.1 %
Reported Power Factor	0.95
Reported Minimum Input Wattage	240 W
Reported Maximum Input Wattage	300
Reported Default Input Wattage	300 W
Voltage Range	120-277 V

PHOTOMETRIC IMAGES AND FILES VIEW DETAILS

SPDX File	<u>Download File</u>

VERSION HISTORY VIEW DETAILS

2023-06-05 Listed 5.1 Premium	
-------------------------------	--