

DesignLights Consortium



Classification	Premium
Primary Use	Architectural Flood and Spot Luminaires
Reported Input Wattage	150.3 W
Reported Light Output	19592 lm
Reported CCT	3000 K
Reported CRI (Ra)	82
Product ID	S-HGKPZJ
DLC Family Code	SLFANA
Listing Status	Listed
Date Qualified	2023-05-04

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-HGKPZJ
Manufacturer	Litetronics International
Brand	Litetronics
Model Number	FL1501
Parent	Yes
Classification	Premium
DLC Family Code	SLFANA
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	High Output
Primary Use Designation	Architectural Flood and Spot Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Exterior Photocell, Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	Yes
Field Adjustable Distribution Type	Integral FALD

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	19592 lm
Reported Efficacy (AC)	130.39 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	82
Reported R9	5
Reported IES Rf	84
Reported IES Rg	96
Reported IES Rcs,h1	-12
Reported Minimum Light Output	19592 lm
Reported Maximum Light Output	19592 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	19592 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	150.3 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	45 W
Reported Maximum Input Wattage	150.3
Reported Default Input Wattage	150.3 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	19041 lm
---------------------	----------

Tested Efficacy (AC)	129.96 lm/W
Tested CCT	3065 K
Tested CRI (Ra)	82
Tested R9	5
Tested IES Rf	84
Tested IES Rg	96
Tested IES Rcs,h1	-12 %
Tested Duv	-0.001
Field Adjustable Light Distribution Setting	No restriction

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	277
Tested Input Wattage	146.5 W
Tested Total Harmonic Distortion	10.3 %
Tested Power Factor	0.951

VERSION HISTORY VIEW DETAILS

2023-05-04	Listed	5.1	Premium
------------	--------	-----	---------