

DesignLights Consortium



Classification	Premium
Primary Use	Parking Garage Luminaires
Reported Input Wattage	40.4 W
Reported Light Output	5317 lm
Reported CCT	4000 K
Reported CRI (Ra)	71
Product ID	PLVOWIJUM0W0
DLC Family Code	QQQVTS
Listing Status	Listed
Date Qualified	2018-05-07

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PLVOWIJUM0W0
Manufacturer	Litetronics International
Brand	Litetronics
Model Number	GL39UR40DLP
Parent	No
Classification	Premium
DLC Family Code	QQQVTS
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	Mid Output
Primary Use Designation	Parking Garage Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
-------------------	----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	5317 lm
Reported Efficacy (AC)	131.61 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	71
Reported R9	-18
Reported IES Rf	72
Reported IES Rg	97
Reported IES Rcs,h1	-14
Reported Default Light Output	5317 lm
Reported BUG Rating	B2 U2 G2

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	40.4 W
Reported Total Harmonic Distortion	14.8 %
Reported Power Factor	0.91
Reported Default Input Wattage	40.4 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2022-08-05	Listed	5.1	Premium
2022-06-30	Delisted	5	Premium
2020-03-30	Listed	5	Premium
2018-11-02	Listed	4.4	Premium
2018-05-07	Listed	4.3	Premium