DesignLights Consortium





Classification	Premium		
Primary Use	Outdoor Non-Cutoff and Semi-Cutoff Wall-Mounted Area Luminaires		
Reported Input Wattage	39.02 W		
Reported Light Output	5449.7 lm		
Reported CCT	3000 K		
Reported CRI (Ra)	80		
Product ID	PL795SAKY1H5		
DLC Family Code	QQQVDB		
Listing Status	Listed		
Date Qualified	2021-03-16		

PRODUCT INFORMATION VIEW DETAILS

Solid State Lighting
5.1
PL795SAKY1H5
MaxLite Inc.
Maxlite, Inc.
WCOP40U-CSBPC
No
Premium
QQQVDB
AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires	
General Application	Mid Output	
Primary Use Designation	Outdoor Non-Cutoff and Semi-Cutoff Wall-Mounted Area Luminaires	

CONTROL FEATURES VIEW DETAILS

Dimming Capability and Range	Continuous Dimming above 10%
Sensor Type	Occupancy Sensor, Exterior Photocell
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	5449.7 lm
Reported Efficacy (AC)	139.66 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	80
Reported R9	-2
Reported IES Rf	83
Reported IES Rg	97
Reported IES Rcs,h1	-14
Reported Minimum Light Output	5449.7 lm
Reported Maximum Light Output	5449.7 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	5449.7 lm
Reported BUG Rating	B1 U3 G4

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	39.02 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	39.02 W
Reported Maximum Input Wattage	39.02
Reported Default Input Wattage	39.02 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2021-04-08	Listed	5.1	Premium
2021-03-31	Listed	5.1	Premium