# **DesignLights Consortium**





Model Number	CP20UP-50[ALL OPTIONS]
Classification	Premium
Primary Use	Parking Garage Luminaires
Reported Input Wattage	20.6 W
Reported Light Output	3001 lm
Reported CCT	5000 K
Reported CRI (Ra)	70
Product ID	S-S7L6JN
DLC Family Code	FFFKQW
Listing Status	Listed
Date Qualified	2024-02-29

### **PRODUCT INFORMATION VIEW DETAILS**

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-S7L6JN
Manufacturer	MaxLite Inc.
Brand	MaxLite Inc.
Model Number	CP20UP-50[ALL OPTIONS]
Parent	No
Classification	Premium
DLC Family Code	FFFKQW
Input Power Type	AC

## **PRODUCT CATEGORIZATION VIEW DETAILS**

Category	Outdoor Luminaires
General Application	Low Output
Primary Use Designation	Parking Garage Luminaires

#### **CONTROL FEATURES VIEW DETAILS**

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	High End Trim
Sensor Type	Exterior Photocell, Multifunction Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	3001 lm
Reported Efficacy (AC)	145.41 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	70
Reported R9	-40
Reported IES Rf	70
Reported IES Rg	89
Reported IES Rcs,h1	-18
Reported Default Light Output	3001 lm
Reported BUG Rating	B1 U3 G1

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	20.6 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Default Input Wattage	20.6 W
Voltage Range	120-277 V

#### **VERSION HISTORY VIEW DETAILS**

2024-02-29	Listed	5.1	Premium
------------	--------	-----	---------