

DesignLights Consortium



Model Number	CP30UP-50[ALL OPTIONS]
Classification	Premium
Primary Use	Parking Garage Luminaires
Reported Input Wattage	31.5 W
Reported Light Output	4366 lm
Reported CCT	5000 K
Reported CRI (Ra)	70
Product ID	S-H6NRMC
DLC Family Code	FFFKQW
Listing Status	Listed
Date Qualified	2024-02-29

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-H6NRMC
Manufacturer	MaxLite Inc.
Brand	MaxLite Inc.
Model Number	CP30UP-50[ALL OPTIONS]
Parent	No
Classification	Premium
DLC Family Code	FFFKQW
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	Low Output
Primary Use Designation	Parking Garage Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	High End Trim
Sensor Type	Exterior Photocell,Multifunction Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	4366 lm
Reported Efficacy (AC)	138.59 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	70
Reported R9	-40
Reported IES Rf	70
Reported IES Rg	89
Reported IES Rcs,h1	-18
Reported Default Light Output	4366 lm
Reported BUG Rating	B2 U3 G2

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	31.5 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Default Input Wattage	31.5 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2024-02-29	Listed	5.1	Premium
------------	--------	-----	---------