

DesignLights Consortium



Model Number	CP70UC-CS[ALL OPTIONS]
Classification	Premium
Primary Use	Fuel Pump Canopy Luminaires
Reported Input Wattage	68.8 W
Reported Light Output	9616 lm
Reported CCT	3000 K
Reported CRI (Ra)	70
Product ID	S-DSPZG4
DLC Family Code	SSSFEX
Listing Status	Listed
Date Qualified	2024-03-13

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-DSPZG4
Manufacturer	MaxLite Inc.
Brand	MaxLite Inc.
Model Number	CP70UC-CS[ALL OPTIONS]
Parent	No
Classification	Premium
DLC Family Code	SSSFEX
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	Mid Output
Primary Use Designation	Fuel Pump Canopy Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	High End Trim
Sensor Type	Exterior Photocell,Multifunction Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	9616 lm
Reported Efficacy (AC)	139.86 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	70
Reported R9	-40
Reported IES Rf	70
Reported IES Rg	89
Reported IES Rcs,h1	-18
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	9616 lm
Reported BUG Rating	B3 U3 G2

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	68.8 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	68.8 W
Reported Maximum Input Wattage	68.8
Reported Default Input Wattage	68.8 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2024-03-13	Listed	5.1	Premium
------------	--------	-----	---------