

DesignLights Consortium



Classification	Premium
Primary Use	Bollards
Reported Input Wattage	22 W
Reported Light Output	2860 lm
Reported CCT	3000 K
Reported CRI (Ra)	80
Product ID	S-7JZQ2A
DLC Family Code	OOOBGG
Listing Status	Listed
Date Qualified	2022-12-21

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-7JZQ2A
Manufacturer	Morris Products Inc.
Brand	Morris
Model Number	72311-72310, 72331-72330
Parent	No
Classification	Premium
DLC Family Code	OOOBGG
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	Low Output
Primary Use Designation	Bollards

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Exterior Photocell
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	Yes
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	2860 lm
Reported Efficacy (AC)	130 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	80
Reported R9	0
Reported IES Rf	83
Reported IES Rg	93
Reported IES Rcs,h1	-12
Reported Minimum Light Output	1560 lm
Reported Maximum Light Output	2860 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	2860 lm
Reported BUG Rating	B1 U3 G2

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	22 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	22 W
Reported Maximum Input Wattage	22
Reported Default Input Wattage	22 W
Voltage Range	120-277 V

VERSION HISTORY VIEW DETAILS

2022-12-21	Listed	5.1	Premium
------------	--------	-----	---------