DesignLights Consortium





Classification	Premium
Primary Use	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires
Reported Input Wattage	100.33 W
Reported Light Output	13765.1 lm
Reported CCT	5000 K
Reported CRI (Ra)	70
Product ID	PSMLZ5H7
DLC Family Code	YYYFAC
Listing Status	Listed
Date Qualified	2021-11-23

PRODUCT INFORMATION VIEW DETAILS

Solid State Lighting
5.1
PSMLZ5H7
Morris Products Inc.
Morris
740[50,86]C
No
Premium
YYYFAC
AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires	
General Application	High Output	
Primary Use Designation	Outdoor Pole/Arm-Mounted Area and Roadway Luminaires	

CONTROL FEATURES VIEW DETAILS

Integral Controls

Dimming Capability and Range	Continuous Dimming to 10% or below		
Integral Control Capability	No Control Capability		
Sensor Type	Exterior Photocell, Sensor Receptacle, Occupancy Sensing		
SSL V5 Wired Communication Protocol	0-10V Analog		
SSL V5 Wireless Communication Protocol	No Wireless Protocol		
Field Adjustable Light Output	No		
White-Tunable	No		
Warm-Dimming	No		
Field Adjustable Light Distribution	Yes		
Field Adjustable Distribution Type	Integral FALD		

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	13765.1 lm
Reported Efficacy (AC)	137.2 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	70
Reported R9	-33
Reported IES Rf	75
Reported IES Rg	95
Reported IES Rcs,h1	-16
Reported Default Light Output	13765.1 lm
Reported BUG Rating	B4 U0 G3

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	100.33 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Default Input Wattage	100 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Field Adjustable Light Distribution Setting	Pointing Straight Down
---	------------------------

VERSION HISTORY VIEW DETAILS

2021-11-23	Listed	5.1	Premium
------------	--------	-----	---------