

# DesignLights Consortium



Classification	Premium
Primary Use	Architectural Flood and Spot Luminaires
Reported Input Wattage	494.59 W
Reported Light Output	68975.1 lm
Reported CCT	5000 K
Reported CRI (Ra)	70
Product ID	S-0MY7DF
DLC Family Code	<a href="#">SLFALB</a>
Listing Status	Listed
Date Qualified	2023-04-04

## PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-0MY7DF
Manufacturer	Morris Products Inc.
Brand	UL - Underwriters Laboratories Inc.
Model Number	77001A
Parent	No
Classification	Premium
DLC Family Code	SLFALB
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	Very High Output
Primary Use Designation	Architectural Flood and Spot Luminaires

## CONTROL FEATURES VIEW DETAILS

Integral Controls	No
-------------------	----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	Yes
Field Adjustable Distribution Type	Integral FALD

## REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	68975.1 lm
Reported Efficacy (AC)	139.46 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	70
Reported R9	-23
Reported IES Rf	74
Reported IES Rg	94
Reported IES Rcs,h1	-16
Reported Default Light Output	68975.1 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	494.59 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Default Input Wattage	494.59 W
Voltage Range	277-480 V

## TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Field Adjustable Light Distribution Setting	Pointing Straight Down
---	------------------------

## VERSION HISTORY VIEW DETAILS

2023-04-04	Listed	5.1	Premium
------------	--------	-----	---------