

DesignLights Consortium



Classification	Premium
Primary Use	Architectural Flood and Spot Luminaires
Reported Input Wattage	731.22 W
Reported Light Output	96687.3 lm
Reported CCT	5000 K
Reported CRI (Ra)	80
Product ID	PBSHO3AF
DLC Family Code	YYEYP
Listing Status	Listed
Date Qualified	2021-10-20

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PBSHO3AF
Manufacturer	Morris Products Inc.
Brand	Morris
Model Number	77016A
Parent	No
Classification	Premium
DLC Family Code	YYEYP
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	Very High Output
Primary Use Designation	Architectural Flood and Spot Luminaires

CONTROL FEATURES VIEW DETAILS

Integral Controls	No
-------------------	----

Dimming Capability and Range	Continuous Dimming above 10%
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	Yes
Field Adjustable Distribution Type	Integral FALD

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	96687.3 lm
Reported Efficacy (AC)	132.23 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	80
Reported R9	-19
Reported IES Rf	73
Reported IES Rg	95
Reported IES Rcs,h1	-16
Reported Default Light Output	96687.3 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	731.22 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Default Input Wattage	731.22 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Field Adjustable Light Distribution Setting	No restriction
---	----------------

VERSION HISTORY VIEW DETAILS

2021-10-20	Listed	5.1	Premium
------------	--------	-----	---------