# DesignLights Consortium







Model Number	77117
Classification	Premium
Primary Use	Architectural Flood and Spot Luminaires
Reported Input Wattage	400 W
Reported Light Output	54540 lm
Reported CCT	5000 K
Reported CRI (Ra)	73
Product ID	S-YC71DW
DLC Family Code	OOOBFN
Listing Status	Listed
Date Qualified	2022-10-26

### **PRODUCT INFORMATION VIEW DETAILS**

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-YC71DW
Manufacturer	Morris Products Inc.
Brand	Morris
Model Number	77117
Parent	No
Classification	Premium
DLC Family Code	OOOBFN
Input Power Type	AC

## PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires
General Application	Very High Output
Primary Use Designation	Architectural Flood and Spot Luminaires

### CONTROL FEATURES VIEW DETAILS

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	Yes
Field Adjustable Distribution Type	Integral FALD

### REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	54540 lm
Reported Efficacy (AC)	136.35 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	73
Reported R9	-29
Reported IES Rf	75
Reported IES Rg	94
Reported IES Rcs,h1	-18
Reported Default Light Output	54540 lm

### REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	400 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Maximum Input Wattage	400
Reported Default Input Wattage	400 W
Voltage Range	200-480 V

### **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

Field Adjustable Light Distribution Setting straight down
---

#### **VERSION HISTORY VIEW DETAILS**

2022-10-26	Listed	5.1	Premium
------------	--------	-----	---------