DesignLights Consortium





| Classification | Premium |
|------------------------|---------------------------|
| Primary Use | Parking Garage Luminaires |
| Reported Input Wattage | 54.1 W |
| Reported Light Output | 7733 lm |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 73 |
| Product ID | S-EV3ODN |
| DLC Family Code | SLFALD |
| Listing Status | Listed |
| Date Qualified | 2023-04-04 |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting |
|--------------------------------|----------------------|
| Technical Requirements Version | 5.1 |
| Product ID | S-EV3ODN |
| Manufacturer | SATCO Products Inc |
| Brand | SATCO |
| Model Number | 65/627R1 |
| Parent | No |
| Classification | Premium |
| DLC Family Code | SLFALD |
| Input Power Type | AC |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Outdoor Luminaires |
|-------------------------|---------------------------|
| General Application | Mid Output |
| Primary Use Designation | Parking Garage Luminaires |

CONTROL FEATURES VIEW DETAILS

| Integral Controls | Yes | |
|-------------------|-----|--|
|-------------------|-----|--|

| Dimming Capability and Range | Continuous Dimming to 10% or below | | |
|--|--------------------------------------|--|--|
| Integral Control Capability | No Control Capability | | |
| Sensor Type | Sensor Receptacle, Occupancy Sensing | | |
| SSL V5 Wired Communication Protocol | 0-10V Analog | | |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol | | |
| Field Adjustable Light Output | No | | |
| White-Tunable | Yes | | |
| Warm-Dimming | No | | |
| Field Adjustable Light Distribution | No | | |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output | 7733 lm |
|-------------------------------|-------------|
| Reported Efficacy (AC) | 143.02 lm/W |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 73 |
| Reported R9 | -16 |
| Reported IES Rf | 73 |
| Reported IES Rg | 98 |
| Reported IES Rcs,h1 | -14 |
| Reported Minimum Light Output | 7733.3 lm |
| Reported Minimum CCT | 3000 K |
| Reported Maximum CCT | 5000 K |
| Reported Default Light Output | 7733 lm |
| Reported BUG Rating | B3 U3 G2 |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 54.1 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 15 % |
| Reported Power Factor | 0.9 |
| Reported Minimum Input Wattage | 54.1 W |
| Reported Maximum Input Wattage | 54.1 |
| Reported Default Input Wattage | 54.1 W |
| Voltage Range | 120-277 V |

VERSION HISTORY VIEW DETAILS

| 2023-04-13 | Listed | 5.1 | Premium |
|------------|--------|-----|---------|
| 2023-04-04 | Listed | 5.1 | Premium |

| 2023-03-29 | Listed | 5.1 | Premium |
|------------|--------|-----|---------|
| | | | |