

DesignLights Consortium



Classification	Premium
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	129.4 W
Reported Light Output	18524 lm
Reported CCT	4000 K
Reported CRI (Ra)	80
Product ID	S-MCW1PF
DLC Family Code	EMWANC
Listing Status	Listed
Date Qualified	2022-04-13

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-MCW1PF
Manufacturer	SATCO Products Inc
Brand	SATCO
Model Number	65/643R1
Parent	No
Classification	Premium
DLC Family Code	EMWANC
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	High-Bay
Primary Use Designation	High-Bay Luminaires for Commercial and Industrial Buildings

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Sensor Receptacle, Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	Yes
Field Adjustable Distribution Type	Integral FALD

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	18524 lm
Reported Efficacy (AC)	143.13 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	80
Reported R9	1
Reported IES Rf	83
Reported IES Rg	96
Reported IES Rcs,h1	-13
Reported Default Light Output	18524 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	129.4 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Default Input Wattage	129.4 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Field Adjustable Light Distribution Setting	Pointing Straight Down
---	------------------------

VERSION HISTORY VIEW DETAILS

2022-04-13	Listed	5.1	Premium
------------	--------	-----	---------