# **DesignLights Consortium**





Classification	Premium
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	219.2 W
Reported Light Output	30315 lm
Reported CCT	4000 K
Reported CRI (Ra)	80
Product ID	S-EYTO90
DLC Family Code	EMWANC
Listing Status	Listed
Date Qualified	2022-04-13

# **PRODUCT INFORMATION VIEW DETAILS**

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-EYTO90
Manufacturer	SATCO Products Inc
Brand	SATCO
Model Number	65/647R1
Parent	Yes
Classification	Premium
DLC Family Code	EMWANC
Input Power Type	AC

#### PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires	
General Application	High-Bay	
Primary Use Designation High-Bay Luminaires for Commercial and Industrial Buildings		

#### **CONTROL FEATURES VIEW DETAILS**

**Integral Controls** 

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Sensor Receptacle, Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	Yes
Field Adjustable Distribution Type	Integral FALD

# REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	30315 lm
Reported Efficacy (AC)	138.28 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	80
Reported R9	2
Reported IES Rf	83
Reported IES Rg	96
Reported IES Rcs,h1	-13
Reported Default Light Output	30315 lm

## REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	219.2 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Default Input Wattage	219.2 W
Voltage Range	120-277 V

#### **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

Tested Voltage for Minimum Efficacy	120
Tested Light Output	30315 lm
Tested Efficacy (AC)	138.28 lm/W
Tested CCT	4025 K
Tested CRI (Ra)	82
Tested R9	2
Tested IES Rf	83

Tested IES Rg	96
Tested IES Rcs,h1	-13 %
Tested Duv	0.0006
Field Adjustable Light Distribution Setting	Pointing Straight Down

# TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Input Wattage	219.2 W
Tested Total Harmonic Distortion	8.9 %
Tested Power Factor	0.943

#### VERSION HISTORY VIEW DETAILS

2022-04-13	Listed	5.1	Premium
------------	--------	-----	---------