DesignLights Consortium





Classification	Premium	
Primary Use	Outdoor Full-Cutoff Wall-Mounted Area Luminaires	
Reported Input Wattage	38.55 W	
Reported Light Output	5120 lm	
Reported CCT	3000 K	
Reported CRI (Ra)	73	
Product ID	PLJ3GZ52DAG2	
DLC Family Code	<u>WWWXHB</u>	
Listing Status	Listed	
Date Qualified	2020-10-06	

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PLJ3GZ52DAG2
Manufacturer	SATCO Products Inc
Brand	SATCO/NUVO
Model Number	65/671
Parent	Yes
Classification	Premium
DLC Family Code	WWWXHB
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires	
General Application	Mid Output	
Primary Use Designation	Outdoor Full-Cutoff Wall-Mounted Area Luminaires	

CONTROL FEATURES VIEW DETAILS

Integral Controls	No	

Dimming Capability and Range	Continuous Dimming above 10%
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	Yes
Warm-Dimming	No
Field Adjustable Light Distribution	No

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	5120 lm
Reported Efficacy (AC)	132.81 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	73
Reported R9	-32
Reported IES Rf	75
Reported IES Rg	94
Reported IES Rcs,h1	-17
Reported Minimum Light Output	5033.67 lm
Reported Maximum Light Output	5120 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	5120 lm
Reported BUG Rating	B1 U2 G1

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	38.55 W
Reported Total Harmonic Distortion	8.97 %
Reported Power Factor	0.9712
Reported Minimum Input Wattage	37.9 W
Reported Maximum Input Wattage	38.55
Reported Default Input Wattage	38.55 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	5020.9 lm
Tested Efficacy (AC)	132.06 lm/W

Tested CCT	3032 K
Tested CRI (Ra)	73
Tested R9	-32
Tested IES Rf	76
Tested IES Rg	95
Tested IES Rcs,h1	-16 %
Tested Duv	-0.0007
Tested Backlight (TM-15 BUG)	1
Tested BUG Rating	B1 U2 G1

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	38.02 W
Tested Total Harmonic Distortion	9.09 %
Tested Power Factor	0.9702

VERSION HISTORY VIEW DETAILS

2021-05-14	Listed	5.1	Premium
2021-03-24	Listed	5.1	Premium
2020-10-06	Listed	5.1	Premium