DesignLights Consortium





Classification	Premium	
Primary Use	Outdoor Non-Cutoff and Semi-Cutoff Wall-Mounted Area Luminaires	
Reported Input Wattage	58.84 W	
Reported Light Output	8207.8 lm	
Reported CCT	3000 K	
Reported CRI (Ra)	80	
Product ID	PL1MK0MX6TQL	
DLC Family Code	EMWAAG	
Listing Status	Listed	
Date Qualified	2021-02-03	

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PL1MK0MX6TQL
Manufacturer	SATCO Products Inc
Brand	SATCO PRODUCTS
Model Number	65/757
Parent	Yes
Classification	Premium
DLC Family Code	EMWAAG
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Outdoor Luminaires	
General Application	Mid Output	
Primary Use Designation Outdoor Non-Cutoff and Semi-Cutoff Wall-Mounted Area Lumi		

CONTROL FEATURES VIEW DETAILS

Integral Controls	Yes
-------------------	-----

Dimming Capability and Range	Continuous Dimming to 10% or below	
Sensor Type	Occupancy Sensor, Exterior Photocell	
SSL V5 Wired Communication Protocol	0-10V Analog	
SSL V5 Wireless Communication Protocol	No Wireless Protocol	
Field Adjustable Light Output	Yes	
White-Tunable	Yes	
Warm-Dimming	No	
Field Adjustable Light Distribution	No	

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	8207.8 lm
Reported Efficacy (AC)	139.5 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	80
Reported R9	3
Reported IES Rf	84
Reported IES Rg	97
Reported IES Rcs,h1	-12
Reported Minimum Light Output	2092.5 lm
Reported Maximum Light Output	8207.8 lm
Reported Minimum CCT	3000 K
Reported Maximum CCT	5000 K
Reported Default Light Output	8207.8 lm
Reported BUG Rating	B1 U4 G5

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	58.84 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Minimum Input Wattage	15 W
Reported Maximum Input Wattage	58.84
Reported Default Input Wattage	58.84 W
Voltage Range	120-347 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Tested Light Output	8073.9 lm
Tested Efficacy (AC)	141.1 lm/W

Tested CCT	2995 K
Tested CRI (Ra)	82
Tested R9	3
Tested IES Rf	84
Tested IES Rg	97
Tested IES Rcs,h1	-12 %
Tested Duv	-0.0018
Tested Backlight (TM-15 BUG)	1
Tested BUG Rating	B1 U4 G5

TESTED ELECTRICAL PERFORMANCE VIEW DETAILS

Tested Voltage	120
Tested Input Wattage	57.21 W
Tested Total Harmonic Distortion	10.12 %
Tested Power Factor	0.961

VERSION HISTORY VIEW DETAILS

2021-05-14	Listed	5.1	Premium
2021-02-03	Listed	5.1	Premium