# **DesignLights Consortium**





| Classification         | Premium   |
|------------------------|---|
| Primary Use            | High-Bay Luminaires for Commercial and Industrial Buildings |
| Reported Input Wattage | 98.9 W  |
| Reported Light Output  | 13838 lm  |
| Reported CCT           | 5000 K  |
| Reported CRI (Ra)      | 84  |
| Product ID             | S-SKO6VH  |
| DLC Family Code        | SLFAIS  |
| Listing Status         | Listed  |
| Date Qualified         | 2023-02-20  |

# **PRODUCT INFORMATION VIEW DETAILS**

| Qualified Draduat List         | Calid Otata Linkting |
|--------------------------------|----------------------|
| Qualified Product List         | Solid State Lighting |
| Technical Requirements Version | 5.1                  |
| Product ID                     | S-SKO6VH             |
| Manufacturer                   | SATCO Products Inc   |
| Brand                          | SATCO                |
| Model Number                   | 65/782R2             |
| Parent                         | No                   |
| Classification                 | Premium              |
| DLC Family Code                | SLFAIS               |
| Input Power Type               | AC                   |

# PRODUCT CATEGORIZATION VIEW DETAILS

| Category                | Indoor Luminaires   |
|-------------------------|---|
| General Application     | High-Bay  |
| Primary Use Designation | High-Bay Luminaires for Commercial and Industrial Buildings |

#### **CONTROL FEATURES VIEW DETAILS**

Integral Controls

| Dimming Capability and Range           | Continuous Dimming to 10% or below   |
|--|--|
| Integral Control Capability            | No Control Capability  |
| Sensor Type                            | Multifunction Sensor, Sensor Receptacle, Daylight Sensing, Occupancy Sensing |
| SSL V5 Wired Communication Protocol    | 0-10V Analog   |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol   |
| Field Adjustable Light Output          | No   |
| White-Tunable                          | No   |
| Warm-Dimming                           | No   |
| Field Adjustable Light Distribution    | Yes  |
| Field Adjustable Distribution Type     | Integral FALD  |

#### **REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

| Reported Light Output         | 13838 lm    |
|-------------------------------|-------------|
| Reported Efficacy (AC)        | 139.96 lm/W |
| Reported CCT                  | 5000 K      |
| Reported CRI (Ra)             | 84          |
| Reported R9                   | 12          |
| Reported IES Rf               | 84          |
| Reported IES Rg               | 95          |
| Reported IES Rcs,h1           | -12         |
| Reported Default Light Output | 13838 lm    |

## **REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS**

| Reported Input Wattage             | 98.9 W    |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 15 %      |
| Reported Power Factor              | 0.9       |
| Reported Maximum Input Wattage     | 98.9      |
| Reported Default Input Wattage     | 98.9 W    |
| Voltage Range                      | 120-277 V |

## TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Field Adjustable Light Distribution Setting | Pointing Straight Down |
|---|------------------------|
|---|------------------------|

## **VERSION HISTORY VIEW DETAILS**

|--|