DesignLights Consortium





Classification	Premium
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	204.9 W
Reported Light Output	28487 lm
Reported CCT	5000 K
Reported CRI (Ra)	84
Product ID	S-GCLY9Z
DLC Family Code	SLFAIS
Listing Status	Listed
Date Qualified	2023-02-20

PRODUCT INFORMATION VIEW DETAILS

Solid State Lighting
5.1
S-GCLY9Z
SATCO Products Inc
SATCO
65/786R2
No
Premium
SLFAIS
AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires
General Application	High-Bay
Primary Use Designation	High-Bay Luminaires for Commercial and Industrial Buildings

CONTROL FEATURES VIEW DETAILS

Integral Controls

Dimming Capability and Range	Continuous Dimming to 10% or below
Integral Control Capability	No Control Capability
Sensor Type	Multifunction Sensor, Sensor Receptacle, Daylight Sensing, Occupancy Sensing
SSL V5 Wired Communication Protocol	0-10V Analog
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	Yes
Field Adjustable Distribution Type	Integral FALD

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	28487 lm
Reported Efficacy (AC)	139.04 lm/W
Reported CCT	5000 K
Reported CRI (Ra)	84
Reported R9	13
Reported IES Rf	84
Reported IES Rg	95
Reported IES Rcs,h1	-11
Reported Default Light Output	28487 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	204.9 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Maximum Input Wattage	204.9
Reported Default Input Wattage	204.9 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Field Adjustable Light Distribution Setting	Pointing Straight Down
---	------------------------

VERSION HISTORY VIEW DETAILS

|--|