DesignLights Consortium





Classification	Premium
Primary Use	High-Bay Luminaires for Commercial and Industrial Buildings
Reported Input Wattage	235 W
Reported Light Output	32796 lm
Reported CCT	4000 K
Reported CRI (Ra)	84
Product ID	S-LPR517
DLC Family Code	SLFAIS
Listing Status	Listed
Date Qualified	2023-02-20

PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	S-LPR517
Manufacturer	SATCO Products Inc
Brand	SATCO
Model Number	65/787R2
Parent	No
Classification	Premium
DLC Family Code	SLFAIS
Input Power Type	AC

PRODUCT CATEGORIZATION VIEW DETAILS

Category	Indoor Luminaires		
General Application	High-Bay		
Primary Use Designation	High-Bay Luminaires for Commercial and Industrial Buildings		

CONTROL FEATURES VIEW DETAILS

Integral Controls

Dimming Capability and Range	Continuous Dimming to 10% or below		
Integral Control Capability	No Control Capability		
Sensor Type	Multifunction Sensor, Sensor Receptacle, Daylight Sensing, Occupancy Sensing		
SSL V5 Wired Communication Protocol	0-10V Analog		
SSL V5 Wireless Communication Protocol	No Wireless Protocol		
Field Adjustable Light Output	No		
White-Tunable	No		
Warm-Dimming	No		
Field Adjustable Light Distribution	Yes		
Field Adjustable Distribution Type	Integral FALD		

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Light Output	32796 lm
Reported Efficacy (AC)	139.55 lm/W
Reported CCT	4000 K
Reported CRI (Ra)	84
Reported R9	13
Reported IES Rf	84
Reported IES Rg	95
Reported IES Rcs,h1	-11
Reported Default Light Output	32796 lm

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	235 W
Reported Total Harmonic Distortion	15 %
Reported Power Factor	0.9
Reported Maximum Input Wattage	235
Reported Default Input Wattage	235 W
Voltage Range	120-277 V

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

|--|

PHOTOMETRIC IMAGES AND FILES VIEW DETAILS

SPDX File

VERSION HISTORY VIEW DETAILS

2023-02-20	Listed	5.1	Premium
------------	--------	-----	---------