DesignLights Consortium





| Classification | Premium |
|------------------------|---|
| Primary Use | High-Bay Luminaires for Commercial and Industrial Buildings |
| Reported Input Wattage | 149.9 W |
| Reported Light Output | 20421 lm |
| Reported CCT | 4000 K |
| Reported CRI (Ra) | 84 |
| Product ID | S-157TJG |
| DLC Family Code | SLFAIT |
| Listing Status | Listed |
| Date Qualified | 2023-02-20 |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting |
|--------------------------------|----------------------|
| Technical Requirements Version | 5.1 |
| Product ID | S-157TJG |
| Manufacturer | SATCO Products Inc |
| Brand | SATCO |
| Model Number | 65/793R2 |
| Parent | No |
| Classification | Premium |
| DLC Family Code | SLFAIT |
| Input Power Type | AC |
| | |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Indoor Luminaires |
|-------------------------|---|
| General Application | High-Bay |
| Primary Use Designation | High-Bay Luminaires for Commercial and Industrial Buildings |

CONTROL FEATURES VIEW DETAILS

Integral Controls

| Dimming Capability and Range | Continuous Dimming to 10% or below |
|--|--|
| Integral Control Capability | No Control Capability |
| Sensor Type | Multifunction Sensor, Sensor Receptacle, Daylight Sensing, Occupancy Sensing |
| SSL V5 Wired Communication Protocol | 0-10V Analog |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol |
| Field Adjustable Light Output | No |
| White-Tunable | No |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | Yes |
| Field Adjustable Distribution Type | Integral FALD |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output | 20421 lm |
|-------------------------------|-------------|
| Reported Efficacy (AC) | 136.23 lm/W |
| Reported CCT | 4000 K |
| Reported CRI (Ra) | 84 |
| Reported R9 | 12 |
| Reported IES Rf | 84 |
| Reported IES Rg | 95 |
| Reported IES Rcs,h1 | -12 |
| Reported Default Light Output | 20421 lm |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 149.9 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 15 % |
| Reported Power Factor | 0.9 |
| Reported Maximum Input Wattage | 149.9 |
| Reported Default Input Wattage | 149.9 W |
| Voltage Range | 120-277 V |

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Field Adjustable Light Distribution Setting | Pointing Straight Down |
|---|------------------------|
|---|------------------------|

VERSION HISTORY VIEW DETAILS

|--|