DesignLights Consortium





| Classification | Premium | |
|------------------------|--|--|
| Primary Use | Outdoor Pole/Arm-Mounted Area and Roadway Luminaires | |
| Reported Input Wattage | 98.5 W | |
| Reported Light Output | 13336 lm | |
| Reported CCT | 4000 K | |
| Reported CRI (Ra) | 85 | |
| Product ID | S-2QF4U0 | |
| DLC Family Code | <u>EMWAYL</u> | |
| Listing Status | Listed | |
| Date Qualified | 2023-04-27 | |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting |
|--------------------------------|----------------------|
| Technical Requirements Version | 5.1 |
| Product ID | S-2QF4U0 |
| Manufacturer | SATCO Products Inc |
| Brand | SATCO/NUVO |
| Model Number | 65/860/5 |
| Parent | No |
| Classification | Premium |
| DLC Family Code | EMWAYL |
| Input Power Type | AC |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Outdoor Luminaires | |
|-------------------------|--|--|
| General Application | High Output | |
| Primary Use Designation | Outdoor Pole/Arm-Mounted Area and Roadway Luminaires | |

CONTROL FEATURES VIEW DETAILS

| Integral Controls | Yes |
|-------------------|-----|
|-------------------|-----|

| Dimming Capability and Range | Continuous Dimming to 10% or below |
|--|---------------------------------------|
| Integral Control Capability | No Control Capability |
| Sensor Type | Exterior Photocell, Occupancy Sensing |
| SSL V5 Wired Communication Protocol | 0-10V Analog |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol |
| Field Adjustable Light Output | No |
| White-Tunable | No |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | No |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output | 13336 lm |
|-------------------------------|------------|
| Reported Efficacy (AC) | 135.4 lm/W |
| Reported CCT | 4000 K |
| Reported CRI (Ra) | 85 |
| Reported R9 | 18 |
| Reported IES Rf | 85 |
| Reported IES Rg | 94 |
| Reported IES Rcs,h1 | -11 |
| Reported Default Light Output | 13336 lm |
| Reported BUG Rating | B5 U3 G2 |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 98.5 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 13.4 % |
| Reported Power Factor | 0.911 |
| Reported Default Input Wattage | 98.5 W |
| Voltage Range | 277-480 V |

PHOTOMETRIC IMAGES AND FILES VIEW DETAILS

| SPDX File | Download File |
|-----------|---------------|
|-----------|---------------|

VERSION HISTORY VIEW DETAILS

| 2023-04-27 | Listed | 5.1 | Premium |
|------------|--------|-----|---------|
|------------|--------|-----|---------|