DesignLights Consortium





| Classification | Premium |
|------------------------|--|
| Primary Use | Outdoor Pole/Arm-Mounted Decorative Luminaires |
| Reported Input Wattage | 97.9 W |
| Reported Light Output | 12262 lm |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 83 |
| Product ID | S-J760DV |
| DLC Family Code | SLFAIO |
| Listing Status | Listed |
| Date Qualified | 2023-02-15 |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting |
|--------------------------------|----------------------|
| Technical Requirements Version | 5.1 |
| Product ID | S-J760DV |
| Manufacturer | SATCO Products Inc |
| Brand | SATCO |
| Model Number | 65/893 |
| Parent | No |
| Classification | Premium |
| DLC Family Code | SLFAIO |
| Input Power Type | AC |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Outdoor Luminaires |
|--|--------------------|
| General Application | High Output |
| Primary Use Designation Outdoor Pole/Arm-Mounted Decorative Luminaires | |

CONTROL FEATURES VIEW DETAILS

| Integral Controls | No |
|-------------------|----|
|-------------------|----|

| Dimming Capability and Range | Continuous Dimming to 10% or below |
|--|------------------------------------|
| Integral Control Capability | No Control Capability |
| Sensor Type | No Sensor |
| SSL V5 Wired Communication Protocol | 0-10V Analog |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol |
| Field Adjustable Light Output | No |
| White-Tunable | Yes |
| Warm-Dimming | No |
| Field Adjustable Light Distribution | Yes |
| Field Adjustable Distribution Type | Integral FALD |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Light Output | 12262 lm |
|-------------------------------|------------|
| Reported Efficacy (AC) | 125.3 lm/W |
| Reported CCT | 3000 K |
| Reported CRI (Ra) | 83 |
| Reported R9 | 7 |
| Reported IES Rf | 85 |
| Reported IES Rg | 96 |
| Reported IES Rcs,h1 | -11 |
| Reported Minimum Light Output | 12262 lm |
| Reported Maximum Light Output | 12262 lm |
| Reported Minimum CCT | 3000 K |
| Reported Maximum CCT | 5000 K |
| Reported Default Light Output | 12262 lm |
| Reported BUG Rating | B3 U3 G2 |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 97.9 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 15 % |
| Reported Power Factor | 0.9 |
| Reported Maximum Input Wattage | 97.9 |
| Reported Default Input Wattage | 97.9 W |
| Voltage Range | 120-347 V |

TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Field Adjustable Light Distribution Setting | Pointing Straight Down | Ī |
|---|------------------------|---|
| | | П |

PHOTOMETRIC IMAGES AND FILES VIEW DETAILS

| SPDX File | Download File | |
|-----------|---------------|--|
|-----------|---------------|--|

VERSION HISTORY VIEW DETAILS