DesignLights Consortium





| Classification | Standard | |
|------------------------|--|--|
| Primary Use | Internal Driver/Line Voltage (UL Type B) Lamps | |
| Reported Input Wattage | 24 W | |
| Reported Light Output | 3200 lm | |
| Reported CCT | 3500 K | |
| Reported CRI (Ra) | 82 | |
| Product ID | PLH6WO8M9CE8 | |
| DLC Family Code | <u>EMWAFW</u> | |
| Listing Status | Listed | |
| Date Qualified | 2021-08-24 | |

PRODUCT INFORMATION VIEW DETAILS

| Qualified Product List | Solid State Lighting | |
|--------------------------------|--------------------------------|--|
| Technical Requirements Version | 5.1 | |
| Product ID | PLH6WO8M9CE8 | |
| Manufacturer | SATCO Products Inc | |
| Brand | SATCO PRODUCTS | |
| Model Number | 24T8/LED/96-835/BP/FA8(S11957) | |
| Parent | No | |
| Classification | Standard | |
| DLC Family Code | EMWAFW | |
| Length | 8.0 ft | |
| Input Power Type | AC | |

PRODUCT CATEGORIZATION VIEW DETAILS

| Category | Linear Replacement Lamp | |
|-------------------------|--|--|
| General Application | T8 Eight-Foot | |
| Primary Use Designation | Internal Driver/Line Voltage (UL Type B) Lamps | |

CONTROL FEATURES VIEW DETAILS

| Integral Controls | No |
|-------------------|----|
|-------------------|----|

| Dimming Capability and Range | Continuous Dimming above 10% | |
|--|------------------------------------|--|
| Integral Control Capability | No Control Capability | |
| Sensor Type | No Sensor | |
| SSL V5 Wired Communication Protocol | Other Wired Communication Protocol | |
| SSL V5 Wireless Communication Protocol | No Wireless Protocol | |
| Field Adjustable Light Output | No | |
| White-Tunable | No | |
| Warm-Dimming | No | |
| Field Adjustable Light Distribution | No | |

REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

| Reported Beam Angle | 210 ° |
|-------------------------------|----------|
| Reported Light Output | 3200 lm |
| Reported Efficacy (AC) | 133 lm/W |
| Reported CCT | 3500 K |
| Reported CRI (Ra) | 82 |
| Reported R9 | 0 |
| Reported IES Rf | 81 |
| Reported IES Rg | 94 |
| Reported IES Rcs,h1 | -13 |
| Reported Default Light Output | 3200 lm |

REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

| Reported Input Wattage | 24 W |
|------------------------------------|-----------|
| Reported Total Harmonic Distortion | 20 % |
| Reported Power Factor | 0.9 |
| Reported Default Input Wattage | 24 W |
| Voltage Range | 120-277 V |

VERSION HISTORY VIEW DETAILS

| 2021-08-24 | Listed | 5.1 | Standard |
|------------|--------|-----|----------|
|------------|--------|-----|----------|