# **DesignLights Consortium**





Classification	Standard	
Primary Use	Dual Mode Internal Driver (UL Type A and Type B)	
Reported Input Wattage	16 W	
Reported Light Output	1900 lm	
Reported CCT	3000 K	
Reported CRI (Ra)	83	
Product ID	PLT0HYEACRK2	
DLC Family Code	SSSEEU	
Listing Status	Listed	
Date Qualified	2021-01-29	

### PRODUCT INFORMATION VIEW DETAILS

Qualified Product List	Solid State Lighting
Technical Requirements Version	5.1
Product ID	PLT0HYEACRK2
Manufacturer	SATCO Products Inc
Brand	Satco
Model Number	S11970
Parent	Yes
Classification	Standard
DLC Family Code	SSSEEU
Input Power Type	AC

### PRODUCT CATEGORIZATION VIEW DETAILS

Category	Linear Replacement Lamp	
General Application	U-Bend Replacement Lamps	
Primary Use Designation	Dual Mode Internal Driver (UL Type A and Type B)	

# **CONTROL FEATURES VIEW DETAILS**

Integral Controls	No
Dimming Capability and Range	Continuous Dimming to 10% or below

Integral Control Capability	No Control Capability
Sensor Type	No Sensor
SSL V5 Wired Communication Protocol	0-10V Analog, Phase Cut, Other Wired Communication Protocol
SSL V5 Wireless Communication Protocol	No Wireless Protocol
Field Adjustable Light Output	No
White-Tunable	No
Warm-Dimming	No
Field Adjustable Light Distribution	No

# REPORTED PHOTOMETRIC PERFORMANCE VIEW DETAILS

Reported Beam Angle	160 °
Reported Light Output	1900 lm
Reported Efficacy (AC)	119 lm/W
Reported CCT	3000 K
Reported CRI (Ra)	83
Reported R9	1
Reported IES Rf	84
Reported IES Rg	94
Reported IES Rcs,h1	-13
Reported Default Light Output	1900 lm

### REPORTED ELECTRICAL PERFORMANCE VIEW DETAILS

Reported Input Wattage	16 W
Reported Total Harmonic Distortion	20 %
Reported Power Factor	0.9
Reported Default Input Wattage	16 W

### **TESTED PHOTOMETRIC PERFORMANCE VIEW DETAILS**

Tested Light Output	1836 lm
Tested Efficacy (AC)	126 lm/W
Tested CCT	2899 K
Tested CRI (Ra)	81
Tested R9	1
Tested IES Rf	84
Tested IES Rg	95
Tested IES Rcs,h1	-12 %
Tested Duv	0.0013

# **TESTED ELECTRICAL PERFORMANCE VIEW DETAILS**

Tested Voltage	120
Tested Input Wattage	14.6 W
Tested Total Harmonic Distortion	12.6 %
Tested Power Factor	0.959

# **VERSION HISTORY VIEW DETAILS**

2022-04-13	Listed	5.1	Standard
2021-01-29	Listed	5.1	Standard